

# Additivo Elasticizzante

## Elastic Additive

### PRODUCT DESCRIPTION

This additive has been formulated with elastomeric resin and specific plastifying agents. It makes fillers, enamels and clearcoats flexible to be applied on bumpers, fascias side, spoilers etc.

### SUBSTRATES

Flexible and semi-flexible plastic supports.

### MIXING

Add the additive in to 2K fillers, enamels and clearcoat with a proportion of about 10 – 30%, depending on the elastic degree of the support. Not recommended for two-coat enamels.

### APPLICATION

Catalyze and dilute the product as referred by technical data sheet without considering the percentage of added additive.

### DRYING

This additive slows down the curing time of the product up to 30%.

### TECHNICAL DATA

Colour	Transparent
Density	0.95 Kg/l
Shelf life	2 years in original tightly closed containers away from direct sunlight and excessive heat. Min storage temperature: 18°C. Max storage temperature: 35°C.



# Additivo Elasticizzante

## Elastic Additive

### CLEAN UP

Clear the equipment carefully with Nitro thinner I 040.

### SAFETY PRECAUTIONS

#### FOR PROFESSIONAL USE ONLY

- Use only in well ventilated areas
- In case of insufficient ventilation, wear suitable respiratory equipment.
- Wear suitable gloves and wash hands immediately after work.
- Comply with the standards in force as to waste disposal.
- See special instructions or safety data sheets.

