1.25

Additivo Texturizzante

Fine Texture (F240) - High Texture (F250)

PRODUCT DESCRIPTION

Solution of well selected texturing compounds that makes 2K enamels and clearcoats opaque and rough, although keeping their chemical and physical characteristics unchanged.

SUBSTRATES

Please refer to the technical data sheet of the product in use.

MIXING

Add the additive in to the product with a proportion of about 50 – 70%.

APPLICATION

Apply with a spray gun (nozzle 1.6 -1.8 mm).

Catalyze and dilute the product as referred by technical data sheet without considering the percentage of added additive.

For two-coat finishes add the additive either in to basecoat or in to clearcoat, not in to both. This additive cuts down the hiding power of the product and slightly changes the colour of it.

DRYING

Please refer to the technical data sheet of the product in use.

TECHNICAL DATA

Colour	Transparent
Density	0.940 Kg/l Fine Texture 0.939 Kg/l High Texture
Dry residue	30%
Shelf life	2 years in original tightly closed containers away from direct sunlight and excessive heat. Min storage temperature: 18°C. Max storage temperature: 35°C.



Rev 050310

Company with Certified Quality System by BVQI according to UNI EN ISO 9001:2000.



1.25

Additivo Texturizzante

Fine Texture (F240) - High Texture (F250)

CLEAN UP

Clear the equipment carefully with Nitro thinner I 040.

SAFETY PRECAUTIONS

FOR PROFESSIONAL USE ONLY

- Use only in well ventilated areas
- In case of insufficient ventilation, wear suitable respiratory equipment.
- Wear suitable gloves and wash hands immediately after work.
- Comply with the standards in force as to waste disposal.
- See special instructions or safety data sheets.



Company with Certified Quality System by BVQI according to UNI EN ISO 9001:2000.

<u>Loggi</u>A Industria Vernici