



LOGGIA
industria vernici

TECHNICAL DATA SHEET

Revision: 10 agosto 2015



Legend

Extra Polished spatula decorative finishing.

General Characteristics

- Composition:** It is high precious spatula decorative refinishing for indoor with a polished marmo effect.
- Recommended Usage:** Suitable for interior finish of ancient or modern buildings artistically interesting, because of its elegance and refinement.

Application

Surface Preparation:



Before applying Legend effect is necessary to prepare the surface properly using powder or paste putty (as Flystuk) sanded, after about 12 hours, with sanding paper (we recommend grain type P120 After sanding is necessary to remove well all the powder and apply 1 coat of acrylic fixative Fissacril diluted by water in the ratio 1:1 / 1:3. After 4-5 hours from the application of the fixative apply, by means of a roller, 2 coats of Universal Primer spaced out by about 5-6 hours each other. The Universal Primer must be white or colored.



Technical applications

Application methods:



American spatula or stainless steel trowel: Ready to use. If necessary, add water for special needs.

Apply 2 coats of Stucco antico veneziano spaced out by 4-6 hours each other taking care to smooth the surface well without polish The finishing coating must be applied overlapping the strokes until the completion of the wall. Finished the wall proceed by polishing it by means of a stainless steel scraper in different directions until you get the desired brightness. For more brightness you can pass the special machine to polish the stucco type p 4000 or a 100% cotton made cloth.

Application temperature:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	0,5 ÷ 1	mm per coat
Touch Dry:	2 - 4	h
Recoatable after:	8	h
Completely cured:	24	h
Tools clearing:	with water	

Painting

The product can be colored with the Tinting Systems L'ANGELO, L'ANGELO OX and MAXXI as well as with universal colorants that are on the market.

It should be mixed different production batches of the same color to prevent possible color differences during the application.

Technical Properties

Density:	1,7 ÷ 1,8	Kg/l
Viscosity:		cPs
pH:	7-8	
Weight Solids:	72%	
Coverage:	13-15	mq/Kg
Colour:	Color chart	
Gloss level:	Brilliant marble	
Pack size:	1 - 5 – 25	Kg

Storage



The unopened product, preserved intact in a dry and cool place, has a shelf life of no less than 24 months.

After use, carefully close the package and store it upside down.

Minimum storage temperature: + 5 ° C

Maximum Storage Temperature: + 30 ° C

Safety Precautions

For all information related to handling of the product and its proper disposal, please refer to the MSDS.

Items of specifications

Extra Polished spatula decorative finishing. Preparation of the surface with a coat of FISSACRIL and two of Universal Primer. Application of three hands of LEGEND with the required quantity to obtain a thickness of the film by dry suitable. Everything must be carried out in accordance with the rules of application, at a cost of € per square meter inclusive of material and installation.

Warnings

The information contained herein is provided to the best of our knowledge. However, such information and suggestions may not have ANY WARRANTY for the applicator, since the conditions of use are outside of our direct control. It is advised to ensure the suitability of the product to the specific case with preliminary tests.

Loggia Industria Vernici S.r.l. Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

Azienda certificata BVQI per il sistema di qualità UNI EN ISO 9001-2000.