




**LOGGIA**  
industria vernici

# TECHNICAL DATA SHEET

Revisione: 11 novembre 2014



## Velluto Fiorentino

Changing velvety coating.

### General Characteristics

**Composition:** Finish of great charm with the reflections of silk and feel of velvet, for fine finishes for both ancient and modern rooms with a high decorative effect.

**Recommended usage:** Suitable for indoor use, such as walls and plaster, pre-treated with acrylic paint.

### Application

**Surface preparation:**





Prepare the surface with powder or pasty putty as (such as Flystuk). After about 12 hours from the end of the application treat with abrasive papers: It is recommended a grain type P120. Apply 1 coat of acrylic fixative FISSACRIL diluted with water 1:1/1:3. After 4-5 hours apply - by a roller - 2 coats of UNIVERSAL PRIMER at an interval of 5-6 hours from one another. The Primer has to be colored in the same shade of the decoration to realize: VELLUTO FIORENTINO



### Application techniques

**Application methods:**

*Stainless steel spatula or trowel:* Product ready to use. For particular needs it can be diluted with water.



After the drying of the Universal primer apply a first coat of Velluto Fiorentino by a steel trowel, uniformly over the entire surface. After 6-8 hours apply a second coat of Velluto Fiorentino uniformly over an area of 2-3 square meters and, still wet, decorate it depending on the desired effect by a crossing movement of the spatula in different directions until you have a silky-velvet effect.

Temperature of application:	+5 ÷ +35	°C
Humidity for application:	< 85%	
Recommended thickness:	0,5 ÷ 1	mm per coat
Touch dry:	4 ÷ 6	h
Recoatable after:	12	h
Completely cured after:	24	h
Tools cleaning:	with water	

## Colouring

---



The product could be colored with Tinting System L'ANGELO and L'ANGELO OX, as well Universal toners that can be found on the market.

It is recommended to mix different batches to avoid possible differences of shades during the application.

## Technical properties

---

Density:	0,9 ÷ 1,0	Kg/l
Viscosity:		cPs
pH:	7-8	
Weight solids:	30%	
Coverage:	7 – 8	mq/l
Color:	Color Folder	
Aspect:	Velvet gold and silver	
Pack size:	0,75 - 4 – 14	l

## Storage

---



Shelf-life: not less than 2 years original tightly closed. Store away from direct sun and excessive heat.

The can should be resealed and stored tightly closed. Store it upside down after use.



Min storage temperature: +5°C

Max storage temperature: +5°C

## Safety Precautions

---

**For all information regarding product use and correct product disposal please refer to Safety Data Sheet.**

---

## Specifications items

Rivestimento cangiante vellutato. Surface preparation with 1 coat of fixative FISSACRIL. Application of 2 coat of Universal primer followed by 2 coats of Velluto fiorentino according to the quantity absorbed by the surface in order to obtain a suitable dry film thickness. All must be made in accordance with the implementing rules, with a cost of € ..... for m2 including material and pose in work.

---

## Warnings

---

All information contained in this data sheet are based on our technical knowledge. However these indication could not have a value of guarantee for applicator considering that conditions of applying of product are out of our control. It is advisable make sure of suitability of the product making previous test.

---

**Loggia Industria Vernici S.r.l.** Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) – ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. [www.loggia.it](http://www.loggia.it), E-mail [commerciale@loggia.it](mailto:commerciale@loggia.it).

**Company with Certified Quality System by BVQI according to UNI EN ISO 9001:2000.**