



Safety Data Sheet

1. Identification of the substance / preparation and the Company

1.1 Identification of the substance or preparation

Code: F2000007
Product name: EXTREME UHS

1.2 Use of the substance / preparation

1.3 Company identification

Name: LOGGIA INDUSTRIA VERNICI S.r.l.
Full address: VIA Colle d'Alba di Levante - B.go S. Donato
District and Country: 04016 SABAUDIA (LT)
ITALIA
Tel.: +39-0773-562212
Fax: +39-0773-562034

e-mail address of the competent person responsible for the Safety Data Sheet: laboratorio@loggia.it

Product distribution by: Loggia Industria Vernici S.r.l.

1.4 Emergency telephone

For urgent inquiries refer to: Centro Antiveleni - Università di Roma, Policlinico Umberto I tel. +39-06-490663

2. Hazards Identification.

2.1 Substance/Preparation Classification.

This product is dangerous under 67/548/EEC and 1999/45/EC directives and subsequent amendments. Therefore, this product requires a safety data sheet according to the Regulation (EC) 1907/2006 and subsequent amendments. Further information on health and/or environmental hazards can be found in sections 11 and 12 of this sheet.

Danger Symbols: F-Xi

R phrases: 11-43-66-67

2.2 Danger Identification.

Because of its chemical-physical features, this product is graded as highly flammable (flash-point below 21 °C).
MAY CAUSE SENSITIZATION BY SKIN CONTACT.
REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.
VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.

3. Composition / Information on ingredients.

Contains:

Name.	Concentration % (C).	Classification.
XILENE (MISCELA DI ISOMERI)	6<= C <7	R 10
C.A.S. number 1330-20-7		Xn R 20/21
EC number 215-535-7		Xi R 38
INDEX number 601-022-00-9		Note C
ACETATO DI 1-METIL-2-METOSSITILE	8<= C <9	R 10
C.A.S. number 108-65-6		Xi R 36
EC number 203-603-9		
INDEX number 607-195-00-7		

**1,2-DICLOROPROPANO**

C.A.S. number 78-87-5
EC number 201-152-2
INDEX number 602-020-00-0

1<= C <1,5

F R 11
Xn R 20/22

N-BUTILE ACETATO

C.A.S. number 123-86-4
EC number 204-658-1
INDEX number 607-025-00-1

24<= C <25,5

R 10
R 66
R 67

NAFTA SOLVENTE (PETROLIO), AROMATICA**LEGGERA**

C.A.S. number 64742-95-6
EC number 265-199-0
INDEX number 649-356-00-4

8,5<= C <10

Xn R 65
Note H P 4

TINUVIN 5151

EC number 400-830-7

1<= C <1,5

Xi R 43
N R 51/53

The complete text of -R- phrases is specified in section 16.

4. First aid measures.

EYES: Irrigate copiously with clean, fresh water for at least 15 minutes. Seek medical advice.

SKIN: Wash immediately with plenty of water. Remove contaminated clothing. If irritation persists, seek medical attention. Wash contaminated clothing before using them again.

INHALATION: Remove to open air. If breathing is irregular, seek medical advice.

INGESTION: Obtain immediate medical attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures.**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health.

Excess pressure may form in containers exposed to fire at a risk of explosion. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water and the remains of the fire according to applicable regulations.

SUITABLE EXTINGUISHING MEDIA

The extinction equipment should contain carbon dioxide, foam or chemical powders. For product leaks and spills that have not caught fire, nebulised water can be used to dispel flammable fumes and protect the individuals taking part in stemming the leak.

EXTINGUISHING MEDIA WHICH SHALL NOT BE USED FOR SAFETY REASONS

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products (carbon oxide, toxic pyrolysis products, etc).

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Hardhat with visor, fireproof clothing (fireproof jacket and trousers with ties around arms, legs and waist) work gloves (fireproof, cut proof and dielectric), self-respirator (self-protector).

6. Accidental release measures.**PERSONAL PRECAUTIONS**

Eliminate sources of ignition (cigarettes, flames, sparks, etc.) from the air in which the leak occurred. If there are no contraindications, spray solid products with water to prevent the formation of dust. Use breathing equipment if fumes or powders are released into the air. Block the leakage if there is no hazard. Do not handle damaged containers or leaked product before donning appropriate protective gear. Send away individuals who are not suitably equipped. For information on risks for the environmental and health, respiratory tract protection, ventilation and personal protection equipment, refer to the other sections of this sheet.

ENVIRONMENTAL PRECAUTIONS

The product must not penetrate the sewers, surface water, ground water and neighbouring areas.

METHODS FOR CLEANING UP

For liquid products, suck into a suitable container (made of material not incompatible with the product) and soak up any leaked product with absorbent inert material (sand, vermiculite, diatomaceous earth, Kieselguhr, etc). Collect the majority of the remaining material and deposit in containers for disposal. For solid products, use spark proof mechanical tools to collect the leaked product and place in plastic containers. If there are no contraindications, use jets of water to eliminate product residues. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.



LOGGIA INDUSTRIA VERNICI S.r.l.

F2000007 - EXTREME UHS

Revision nr.5
Dated 01/04/2010
Printed on 07/04/2010
Page n. 3 / 6

EN

7. Handling and storage.

Store in a well ventilated place, keeping the containers closed when not used. Do not smoke while handling. Keep far away from sources of heat, bright flames and sparks and other sources of ignition.

8. Exposure control / personal protection.

8.1 Exposure limit values.

Name	Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	
XILENE (MISCELA DI ISOMERI)	TLV-ACGIH		434		651		Skin
	OEL	EU	221	50	442	100	Skin
	OEL	IRL		50		100	Skin
	WEL	UK		50		100	Skin
ACETATO DI 1-METIL-2-METOSSITILE	OEL	EU	275	50	550	100	Skin
	OEL	IRL		50		100	Skin
	WEL	UK		50		100	Skin
1,2-DICLOROPROPANO	TLV-ACGIH		347		508		
	OEL	IRL		75		110	
N-BUTILE ACETATO	TLV-ACGIH		713		950		
	OEL	IRL		150		200	
	WEL	UK		150		200	

8.2 Exposure controls.

As the use of adequate technical equipment must always take priority over personal protection equipment, make sure that the workplace is well aired through effective local aspiration or bad air vent. If such operations do not make it possible to keep the concentration of the product below the permitted workplace exposure thresholds a suitable respiratory tract protection must be used. See product label for hazard details during use.

Ask your chemical substance suppliers for advice when choosing personal protection equipment. Personal protection equipment must comply with the rules in force indicated below.

HAND PROTECTION

Protect hands with category II (ref. Directive 89/686/EEC and standard EN 374) work gloves, such as those in PVC, neoprene, nitril or equivalent.

The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.

EYE PROTECTION

Wear protective airtight goggles (ref. standard EN 166).

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN 344). Wash body with soap and water after removing overalls.

RESPIRATORY PROTECTION

If the threshold value for one or more of the substances present in the preparation for daily exposure in the workplace or to a fraction established by the company's prevention and protection service is exceeded, wear a mask with an B or universal filter, the class (1, 2 or 3) of which must be chosen according to the limit concentration of use (ref. standard EN 141).

The use of breathing protection equipment, such as masks with organic vapour and dust/mist cartridges, is necessary in the absence of technical measures limiting worker exposure. The protection provided by masks is in any case limited.

If the substance in question is odourless or its olfactory threshold is higher than the relative exposure limit and in the event of an emergency, or when exposure levels are unknown or the concentration of oxygen in the workplace is less than 17% volume, wear self-contained, open-circuit compressed air breathing apparatus (ref. standard EN 137) or fresh air hose breathing apparatus for use with full face mask, half mask or mouthpiece (ref. standard EN 138).

An emergency eye washing and shower system must be provided.

**9. Physical and chemical properties.**

Solid on weight	
colour	transparent
Solubility	soluble in solvent
Odour	of solvent
physical state	liquid
pH.	Not available.
Boiling point.	Not available.
Flash point.	< 21 °C.
Explosive properties.	Not available.
Vapour pressure.	Not available.
Specific gravity.	1,000 Kg/l

10. Stability and reactivity.

The product is stable in normal conditions of use and storage. When heated or in the event of a fire, carbon oxides may be released and vapours which are dangerous to health. The vapours may also form explosive mixtures with the air.

Xylene is stable but may give violent reactions if placed in contact with strong oxidants such as nitric acid, sulfuric acid, perchlorates and similar agents. It is biodegradable in water and decomposes in the sunlight (photodegradable).

1-methyl-2-methoxyethyl acetate: it is stable but in presence of air, it can gradually form peroxides which explode due to the rise in temperature. It can react violently with oxidizing agents and strong acids and alkaline metals. Avoid copper, aluminium and their alloys when storing. Store under inert atmosphere, repaired from humidity because it easily hydrolyses.

Dichloropropane decomposes on contact with flames or redhot surfaces giving off toxic vapours of phosgene and corrosive vapours of hydrochloric acid. It reacts with light metals (aluminium etc..) developing heat.

Nbutyl acetate easily decomposes with water especially when heated.

11. Toxicological information.

Upon contact with skin, this product causes sensitization (dermatitis). Dermatitis derives from skin irritation on the areas which repeatedly come into contact with the sensitizing agent. Cutaneous lesions may include: erythemas, edemas, papules, vesicles, pustules, scurries, ulcerations and exudative phenomena, whose intensity varies according to illness seriousness and affected areas. Erythemas, edemas and exudative phenomena prevail during the acute phase. Scuffy skin, dryness, ulcerations and skin thickening prevail during the chronic phase.

This product may have a degreasing action on the skin, producing dryness and chapped skin after repeated exposure.

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

N-butyl acetate: the vapours are particularly irritating to the eyes and respiratory tract and at high concentrations they are also narcotic. Frequent contact with the skin may cause dermatitis (INR nr. 31, 1987).

2-METHOXY-1-METHYLETHYL ACETATE: oral LD50 (mg/kg) > 5000 (RAT) ; dermal LD50 (mg/kg) > 5000 (RAT).

12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

13. Disposal consideration.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information.

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations.

These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and unloading dangerous goods must be trained on all the risks deriving from these substances and on all

actions that must be taken in case of emergency situations.

Road and rail transport:

ADR/RID Class: 3 UN: 1263
 Packing Group: II
 Label: 3
 Nr. Kemler: 33
 Limited Quantity: LQ06
 Tunnel restriction code: (D/E)
 Proper Shipping Name: PAINT or PAINT RELATED MATERIAL
 Special Provision: 640D



Carriage by sea (shipping):

IMO Class: 3 UN: 1263
 Packing Group: II
 Label: 3
 EMS: F-E S-E
 Marine Pollutant: NO
 Proper Shipping Name: PAINT or PAINT RELATED MATERIAL



Transport by air:

IATA: 3 UN: 1263
 Packing Group: II
 Label: 3
 Cargo:
 Packaging instructions: 307 Maximum quantity: 60 L
 Pass.:
 Packaging instructions: 305 Maximum quantity: 5 L
 Special Instructions: A3, A72
 Proper Shipping Name: PAINT or PAINT RELATED MATERIAL



15. Regulatory information.

Xi



IRRITANT

F



HIGHLY FLAMMABLE

- R 11 HIGHLY FLAMMABLE.
- R 43 MAY CAUSE SENSITIZATION BY SKIN CONTACT.
- R 66 REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.
- R 67 VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.
- S 9 KEEP CONTAINER IN A WELL-VENTILATED PLACE.
- S 16 KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.
- S 24 AVOID CONTACT WITH SKIN.
- S 33 TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES.
- S 37 WEAR SUITABLE GLOVES.
- S 43 IN CASE OF FIRE, USE . . . (INDICATE IN THE SPACE THE PRECISE TYPE OF FIRE-FIGHTING EQUIPMENT. IF WATER INCREASES RISK, ADD - 'NEVER USE WATER').

Contains: TINUVIN 5151

Danger labelling under directives 67/548/EEC and 1999/45/EC and following amendments and adjustments.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.



VOC (Directive 2004/42/EC) :
Topcoat - All types.
VOC given in g/litre of product in a ready-to-use condition :
Limit value: 420,00
VOC of product : 250,00

16. Other information.

Text of -R- phrases quoted in section 3 of the sheet.

R 10	FLAMMABLE.
R 11	HIGHLY FLAMMABLE.
R 20/21	HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.
R 20/22	HARMFUL BY INHALATION AND IF SWALLOWED.
R 36	IRRITATING TO EYES.
R 38	IRRITATING TO SKIN.
R 43	MAY CAUSE SENSITIZATION BY SKIN CONTACT.
R 51/53	TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.
R 65	HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.
R 66	REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.
R 67	VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.

GENERAL BIBLIOGRAPHY

1. Directive 1999/45/EC and following amendments;
2. Directive 67/548/EEC and following amendments and adjustments (technical adjustment XXIX);
3. Regulation (EC) 1272/2008 (CLP) of the European Parliament;
4. Regulation (EC) 1907/2006 (REACH) of the European Parliament;
5. The Merck Index. - 10th Edition;
6. Handling Chemical Safety;
7. Niosh - Registry of Toxic Effects of Chemical Substances;
8. INRS - Fiche Toxicologique (toxicological sheet);
9. Patty - Industrial Hygiene and Toxicology;
10. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition;

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product .

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Changes to previous review.

The following sections were modified:

01 / 09